

End-customer price list, prices given exclude VAT

AMK-SOLAC Systems AG



OPC 15



Contents Collectors / mounting / accessories

OPC collectors	1.0	Page	3
OPC tiled roof mounting system	2.1	Page	4
OPC flat roof mounting system	2.2	Page	5
OPC folded seam roof mounting system	2.3	Page	6
OPC Eternit roof mounting system	2.4	Page	7
OPC connection system	3.0	Page	8
Control systems	4.0	Page	9
Pumps and fittings	5.0	Page 1	1

Appendix:

General Terms and Conditions

6.0 Page 14



Detailed descriptions can be found in the tender documents

Product No.

10.4007

Price in EUR (excl. VAT)

954.00

1 OPC collectors

Note

Modules are delivered pre-assembled



OPC 10 evacuated solar module

-1.45 m² gross surface area

- -1.15 m² aperture area
- -1.67 m² active absorber area
- -10 tubes, 1505 mm



OPC 15 evacuated solar module

-2.13 m² gross surface area

- -1.72 m² aperture area
- -2.51 m² active absorber area
- -15 tubes, 1505 mm

10.4008

1295.00

Evacuated tube, 47/37 mm - 1505 mm (15 pcs. replacement tubes in box)

345.00



Product No.

10.1102

10.1152

110.00

122.00

Price in EUR (excl. VAT)

2. OPC mounting system

2.1 tiled roof




V2A/ALU stainless steel hooks and mounting angles



Z10 basic tiled roof mounting set 10.1101 133.00

- 1 set of 4 collector hooks
- 4 height-adjustable mounting angles
- 1 set of 2 S profiles, length 0.905 m
10.4145
10.4145
10.4145
10.4145




Z10plus advanced tiled roof mounting set

- 1 set of 4 collector hooks 10.4145
- 2 height-adjustable mounting angles 10.4074
- 1 set of 2 S profiles, length 0.905 m 10.4127
- 2 profile connectors 10.4139

geeignet für OPC 15

Z15 basic tiled roof mounting set 10.1151 142.00

- 1 set of 4 collector hooks
- 4 height-adjustable mounting angles
- 1 set of 2 S profiles, length 1.305 m
10.4145
10.4074
10.4128



Z15plus advanced tiled roof mounting set

- 1 set of 4 collector hooks
- 2 height-adjustable mounting angles
- 1 set of 2 S profiles, length 1.305 m
- 2 profile connectors
10.4128
- 2 profile connectors

Product No.

Price in EUR (excl. VAT)

OPC mounting system

2.2 flat roof



Aluminium profiles and mounting plates V2A stainless steel screws

- 2 single supports, pre-assembled



F10/15 basic flat roof mounting system

10.4121

140.00

- as a set on the outside - 4 clamping plates with concrete anchor, nut,
- and washer

geeignet für OPC

F10/15 advanced flat roof mounting system

- 1 double support, pre-assembled as a set on the inside 10.4122

- 2 clamping plates with concrete anchor, nut, and washer

10.1162

10.1161


130.00

Extra base plate fastening for flat roof mounting

- 1 x clamping plate

- 1 x concrete anchor with nut and washer

10.4120





Product No.

Price in EUR (excl. VAT)


127.00

OPC mounting system

2.3 folded seam roof

- 1 set of 4 collector hooks

Aluminium profiles and collector hooks V2A stainless steel screws




B10 basic folded seam roof mounting set

10.1171

10.4145 10.4141


4 clamping pieces with bracket
1 set of 2 S profiles, length 0.905 m
10.4141
10.4127



B10plus advanced folded seam roof mounting set

10.1172 107.00

- 1 set of 4 collector hooks
- 2 clamping pieces with bracket
- 1 set of 2 S profiles, length 0.905 m
- 2 profile connectors
10.4141
10.4127
2 profile connectors



B15 basic folded seam roof mounting set

10.1571

133.00

- 1 set of 4 collector hooks
- 4 clamping pieces with bracket
- 1 set of 2 S profiles, length 1.305 m
10.4145
10.4145
10.4141



B15plus advanced folded seam roof mounting set

10.1572

mounting set	
- 1 set of 4 collector hooks	10.4145
- 2 clamping pieces with bracket	10.4141
- 1 set of 2 S profiles, length 1.305 m	10.4128
- 2 profile connectors	10.4139


Product No.

Price in EUR (excl. VAT)

OPC mounting system

2.4 Eternit roof


Aluminium profiles and collector hooks V2A stainless steel bracket plates and screws



E10 basic Eternit roof mounting set

10.1181 137.00


- 1 set of 4 collector hooks
- Set of 4 Eternit/wall screws
- Set of 4 bracket plates
- 1 set of 2 S profiles, length 0.905 m
10.4153
10.4127



E10plus advanced Eternit roof mounting set

10.1182 115.00


- 1 set of 4 collector hooks 10.4145
- Set of 2 Eternit/wall screws 10.4052
- Set of 2 bracket plates 10.4153
- 1 set of 2 S profiles, length 0.905 m 10.4127
- 2 profile connectors 10.4139



E15 basic Eternit roof mounting set

10.1581 145.00

- 1 set of 4 collector hooks 10.4145
- Set of 4 Eternit/wall screws 10.4052
- Set of 4 bracket plates 10.4153
- 1 set of 2 S profiles, length 1.305 m 10.4128



geeignet für OPC

E15plus advanced Eternit roof mounting set


10.1582 123.00

- 1 set of 4 collector hooks	10.4145
- Set of 2 Eternit/wall screws	10.4052
- Set of 2 bracket plates	10.4153
- 1 set of 2 S profiles, length 1.305 m	10.4128
- 2 profile connectors	10.4139

Product No.

Price in EUR (excl. VAT)

3. OPC connection system



T10/15 basic Tichelmann hydraulic set with U-bend, 2 blind caps, seals and sensor

- 1 U-bend, incl. seals and screw connection


10.2061 - 2 blind caps, incl. seals

- 1 PTP6 collector sensor

10.2031 67.00

10.2062


50.5031



3 expansion joints (collector connectors)

- 3 expansion joints, 3/4", incl. vented seals 18x24 mm

10.2032 49.00




3/4" connection set - W 20 mm L 500 mm

- 2 corrugated pipes, 3/4"-3/4", incl. 4 vented seals 18x24 mm

- 2 soldered connections 3/4" to 20 mm for pipe connection

10.2053 76.00

1 expansion joint, 3/4" incl. 2 vented seals 18x24 mm	10.2063	18.00
1 expansion joint set 18x24 mm, high-temperature resistant (5 pcs.)	10.2066	5.00
1 pane seal set 25.5x1.6mm, high-temperature resistant (5 pcs.)	10.2067	5.00
Hydraulic cover Aluminium cover for the mounting between the	10.2041	21.00



OPC-collectors, with insulating material and clamp fitting

Product No.

50.5001

50.5002

Price in EUR (excl. VAT)

190.00

283.00

4. Control systems



AMK-Basic solar controller

For single-circuit systems with all basic functions

- self-explanatory pictograms
- large multifunctional LCD display
- easy operation
- digitally adjustable controller parameters
- RPM control or switch control
- integrated operating hours counter
- system monitoring



AMK-Vision solar controller

For multi-circuit systems and added convenience in measurement and operation


- self-explanatory pictograms
- large multifunctional LCD display
- easy operation
- digitally adjustable controller parameters
- RPM control or switch control
- special functions, e.g. for frost protection, thermostat for heating
- integrated operating hours counter
- system monitoring
- energy yield measurement
- various protection functions
- third switched output



AMK-Genius solar controller

For multi-circuit systems and added convenience in measurement and operation

- self-explanatory pictograms
- large multifunctional LCD display
- easy, menu-driven operation
- specifications and controller parameters are digitally adjustable
- integrated operating hours counter
- system monitoring
- integrated energy yield measurement
- various protection functions
- DataStick® data entry interface



Collector /universal sensor

(250° platinum, black)

PT1000 pipe sensor with silicone cable and 2 pcs. cable ties 50.5072 up to +125°C supplied

50.5031

50.5003

16.00


475.00

	Product No.	Price in EUR (excl. VAT)
PSF3 radiation sensor	50.5050	103.00
Flow sensor set With 1 litre/pulse, nominal flow rate 1.5 /h, up to 90°C, R1/2" (not suitable for bypass systems)	50.5070	145.00
With 1 litre/pulse, nominal flow rate 0.6 /h, up to 120°C, R1/2"	50.5071	271.00
A PT1000 pipe sensor with a silicone cable and 2 pcs. cable ties up to +125°C is supplied with every flow sensor set		
CAUTION: When installing the flow sensor, make sure to also install the dirt trap.		

Product No.

Price in EUR (excl. VAT)

5. Pumps and fittings




AMK pump group OSS I Type 1-60/6.0 mwc/ 1.5-6.0l/min. (single-string)

50.6004

245.00

- 1 Grundfos/WILO, 3-stage pump
- 1 connector ET-1"
- 1 ball valve with wing grip (int. check valve, boiler fill/empty)
- 1 inline taco setter 1.5-6.0l/min.
- 1 dial thermometer 0-160° C
- 1 connection for expansion cylinder ET-3/4"




AMK pump group OSS I Type 1-60/6.0 mwc/ 4.0-16.0l/min. (single-string)

50.6005

245.00

- 1 Grundfos/WILO, 3-stage pump
- 1 connector ET-1"
- 1 ball valve with wing grip (int. check valve, boiler fill/empty)
- 1 inline taco setter 4.0-16.0l/min.
- 1 dial thermometer 0-160° C
- 1 connection for expansion cylinder ET-3/4"



AMK pump group OSS II Type 2-60/6.0 mwc/ 1.5-6.0l/min. (double-string)

50.6007

373.00

Cold side (right string)


- 1 connector ET-1"
- 1 ball valve with wing grip (int. check valve, boiler fill/empty)
- 1 Grundfos/WILO, 3-stage pump
- 1 inline taco setter 1.5-6.0l/min.
- 1 dial thermometer 0-160° C
- 1 connection for expansion cylinder ET-3/4"

Hot side (left string)

- 1 connector ET-1"
- 1 ball valve with wing grip (int. check valve, ½", 6 bar)
- 1 deaerator with 1/4" valve, 0-10 bar manometer
- 1 dial thermometer, 0-160° C
- 1 connector ET-1"

Product No.

Price in EUR (excl. VAT)



AMK pump group OSS II Type 2-60/6.0 mwc/ 4.5-16.0 l/min. (double-string)

50.6006

373.00

Cold side (right string)

- 1 connector ET-1"
- 1 ball valve with wing grip (int. check valve, boiler fill/empty)
- 1 Grundfos/WILO, 3-stage pump
- 1 inline taco setter 4.5-16.0l/min.
- 1 dial thermometer 0-160° C
- 1 connection for expansion cylinder ET-3/4"

Hot side (left string)

- 1 connector ET-1"
- 1 ball valve with wing grip (int. check valve, ½", 6 bar)
- 1 deaerator with 1/4" valve, 0-10 bar manometer
- 1 dial thermometer, 0-160° C
- 1 connector ET-1"



Twinway Solar helical tube


TWS Solar S DN15, with sensor cable connection diameter 1/2" union nut 3/4"

- flexible stainless steel helical tube, length 12.5 m	10.2054	595.00
- flexible stainless steel helical tube, length 15.0 m	10.2055	735.00



Regulating and shut-off valve


vvitn R ¾ bypass		
- SD 2-8 balancing valve	50.6024	145.00
- SD 8-40 balancing valve	50.6025	148.00



REGUSOL filli

To be installed in the solar circuit at the lowest point in the system.

ing and flushing device	50.6008	44.00
the solar circuit at the lowest point in the		




Compression fitting

For REGUSOL, size 1"/22 mm

50.6011

Product No.

Price in EUR (excl. VAT)




Soldered connection

To connect R $\frac{1}{2}$ " thread to 20mm collector connection with 1 vented seal (high-temperature resistant)

50.5022

4.00



Tyfocor

LS heat transfer fluid (ready-mixed) 20 Litre canister

50.5102

81.00



Profi Solar filling and flushing unit

Trolley-mounted solar filling and flushing station Key data:

- flow rate: max. 2.1 /h at 2900 RPM.
- flow pressure: max. 4.0 bar at 2900 RPM.
- flow height: max. 40 mwc = 4 bar = 400 kPa
- dimensions: HxWxD 102x42x52 cm

50.6102

Upon request

